

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-082982

(43)Date of publication of application : 30.03.2001

(51)Int.Cl.

G01D 5/245

G01B 7/00

G01B 7/30

(21)Application number : 11-256167

(71)Applicant : CKD CORP

(22)Date of filing : 09.09.1999


(72)Inventor : FUJITA EIJI

(54) RESOLVER ROTATING POSITION DETECTING DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a resolver rotating position detecting device capable of detecting and identifying a plurality of abnormalities.

SOLUTION: A CPU 9 provided in the computer 8 of this resolver rotating position detecting device 1 receives from an RD converter 21 the input of position detection data matching each resolver 3, 4, 5. The CPU 9 reads from a flash memory 10 a measured voltage matching the position detection data. The CPU 9 receives through an AD converter 15 the input of a feedback signal value matching each resolver 3, 4, 5, and obtains a voltage value of the feedback signal. When determining that the difference between the voltage value of the feedbacks signal and the measured voltage is out of a permissible range, the CPU 9 determines that an abnormality has occurred, and identifies the kind of abnormality from the voltage value of the feedback signal. In the event of an abnormality, the CPU 9 actuates an alarm 18 and a display device 17 to let an operator know the kind of abnormality.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's]

BEST AVAILABLE COPY

decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

BEST AVAILABLE COPY